



# MICROKIOSK IMAGO A10



# IMAGO

## IMAGO A10 is a compact all-in-one computer for digital signage applications.

It is equipped with a 10.1" touch screen and it's powered by Android 8.0 Oreo. The device is VESA mount system compliant. Built-in Wi-Fi and Bluetooth modules allows to transfer data with a cloud. Together with an integrated area imager, Imago A10 will be able to read data from any product identifiers. This can be used for recording work time and confirming presence, checking current status or stock levels in shops. Imago A10 ensures reliable operation in customer service points.



VESA compliant



Power over Ethernet



Area imager

## TECHNICAL SPECIFICATION

<b>HARDWARE</b>	CPU	ROCKCHIP RK-3288 ARM CORTEX-A17, QUAD CORE
	GPU	MALI-T764, TE, ASTC, AFBC TECHNOLOGY
	Storage	8 GB eMMC
	RAM	2 GB DDR3 SDRAM
<b>DISPLAY</b>	Size	10.1"
	Resolution	1280 x 800
	Technology	TFT LCD
	Touch	10-POINT MULTI-TOUCH PANEL
<b>I/O</b>	External storage	SD CARD (SDHC CLASS10)
	USB	1 x USB 2.0 1 x MICRO USB OTG
	Ethernet	1 PORT 10/100/1000 M
	PoE	OPTIONAL 802.3 AT TYPE 2 (POE+)
	WLAN	WI-FI: IEEE 802.11a/b/g/n/ac
	Bluetooth	BT 4.2
<b>ACCESSORIES</b>		ZEBRA SE-2707 2D SCANNER, NFC READER, LED SIDE PANELS
<b>AUDIO</b>	Speakers	2 x 2 W SPEAKERS + 2 x 1.25 W AMPLIFIERS
	Line Out	1 x JACK 3.5 MM
<b>SOFTWARE</b>	OS	ANDROID 8.1 OREO
<b>POWER SUPPLY</b>	Power	20 W
	Voltage	100-240 V, 2 A MAX. 50-60 Hz, DC 12 V ±5%
<b>INSTALLATION TYPE</b>	VESA standard	75 x 75
<b>ENVIRONMENT</b>	Temperature	OPERATION: 0°C ~ 40°C (32°F ~ 104°F), STORAGE: -10°C ~ 55°C (14°F ~ 131°F)
	Humidity	10% ~ 85% (NON-CONDENSING)
<b>DIMENSIONS</b>	Width, height, depth (mm)	252.1 x 177.8 x 24
	Weight	608 g / 644 g (including barcode reader)